


Technical Specification



Tough Beacon TB18-2

Dimensions	Length Width Height	94 mm 58 mm 35 mm
Microcontroller		Nordic Semiconductor nRF52832
Connectivity	Bluetooth Range Available transmission power levels Sensitivity	Bluetooth 4.2 compliant, Bluetooth 5 ready up to 70 meters 1 (-20dBm), 2 (-16dBm), 3 (-12dBm), 4 (-8dBm), 5 (-4dBm), 6 (0dBm), 7 (4dBm) -93dBm
Battery and Power		Two CR2477 Lithium Manganese Dioxide Coin Battery with capacity of 1000 mAh each - battery powered device lifetime up to 60 months Batteries are replaceable
Sensors		Temperature, Accelerometer (3-axis)
Casing	Material Colours Protection Splashproof Dustproof Fire class	PC Light grey IP-65 Yes Yes UL 94 HB
Environmental Requirements	Operating Temperature Storage temperature Humidity (non-condensing)	-20°C / + 60°C (-4°F / +140°F) -5°C / +35°c (23°F / +95°F) from 0% up to 95%
Warranty		12 months
Beacon standards compatibility**	iBeacon Eddystone Kontakt.io Secure Profile	Yes Yes Yes Custom frames possible for large orders

* please contact sales

** All packets can be enabled and disabled at any time, except Kontakt.io Secure Profile (it's constantly broadcasted at a fixed 1000ms interval)

Battery life*

Tx Power / Interval (ms)	Tx=3 (-12 dbm)	Tx=7
1000 ms	86 months	60 months
800 ms	78 months	55 months
500 ms	61 months	43 months
350 ms	50 months	34 months

*Estimated battery life at the room temperature.

Get in Touch



- ✓ kontakt@kontakt.io
- facebook.com/kontakt.io
- 🔰 @kontakt_io
- +48 123 793 445
- Ø Kontakt.io Stoczniowców 3, 30-709 Kraków, Poland

